

LİNEA-RODEO MODEL TEKNİK ÖZELLİKLERİ

Tip	Yükseklik (H)	Boyutlar (mm)			Ağırlık kg/m	Su Hacmi Lt/m	Isı Gücü				
		Eksen Aralığı (h)	Derinlik	Uzunluk (min-max) (L)			Δ	T=60 °C 90-70/20 °C		Δ T=60 °C 75-65/20 °C	
								kcal/h	Watt	kcal/h	Watt
DP 20040000	1400	345	70	400	26,39	5,88	842,65	980	674,12	784	
	1500				28,28	6,30	902,84	1050	722,27	840	
	1600				30,15	6,72	963,03	1120	770,42	896	
	1700				32,00	7,14	1023,22	1190	818,57	952	
	1800				33,91	7,56	1083,40	1260	866,72	1008	
DP 20040000 Orta Giriş	1400	50-345	70	400	30,87	5,88	842,65	980	674,12	784	
	1500				33,10	6,30	902,84	1050	722,27	840	
	1600				35,27	6,72	963,03	1120	770,42	896	
	1700				37,47	7,14	1023,22	1190	818,57	952	
	1800				39,67	7,56	1083,40	1260	866,72	1008	
DP 20050000	1400	445	70	500	36,65	6,72	1053,31	1225	842,65	980	
	1500				39,27	7,20	1128,98	1313	902,84	1050	
	1600				41,87	7,68	1203,78	1400	963,03	1120	
	1700				44,49	8,16	1279,45	1488	1023,22	1190	
	1800				47,09	8,64	1354,26	1575	1083,40	1260	
DP 20050000 Orta Giriş	1400	50-445	70	500	38,61	6,72	1053,31	1225	842,65	980	
	1500				41,37	7,20	1128,98	1313	902,84	1050	
	1600				44,11	7,68	1203,78	1400	963,03	1120	
	1700				46,87	8,16	1279,45	1488	1023,22	1190	
	1800				49,61	8,64	1354,26	1575	1083,40	1260	
DP 20060000	1400	545	70	600	43,03	7,56	1435,94	1670	1148,75	1336	
	1500				46,10	8,10	1538,26	1789	1230,44	1431	
	1600				49,16	8,64	1640,58	1908	1312,12	1526	
	1700				52,23	9,18	1742,91	2027	1394,67	1622	
	1800				55,29	9,72	1846,09	2147	1476,35	1717	
DP 20060000 Orta Giriş	1400	50-545	70	600	45,69	7,56	1435,94	1670	1148,75	1336	
	1500				48,95	8,10	1538,26	1789	1230,44	1431	
	1600				52,20	8,64	1640,58	1908	1312,12	1526	
	1700				55,46	9,18	1742,91	2027	1394,67	1622	
	1800				58,71	9,72	1846,09	2147	1476,35	1717	